



Broadband Amplifiers



Range: AM-5000



NEW

OPTION

Rejection

5G

READY



VHF-UHF Separated Amplification

Automatic Dc to Pré-amplifier



232x94x53mm

REF.	AM - 5001	AM - 5002	AM - 5002 IT	AM - 5003	AM - 5021	AM - 5031
INPUTS	5			1	4	3
BAND RANGE	MHz	MHz	MHz	MHz	MHz	MHz
GAIN	dB	dB	dB	dB	dB	dB
ADJUSTABLE GAIN RANGE	dB	dB	dB	dB	dB	dB
MAXIMUM OUTPUT LEVEL	dBμV	dBμV	dBμV	dBμV	dBμV	dBμV
RETURN PATH	MHz	MHz	MHz	MHz	MHz	MHz
MAINS VOLTAGE	VAC	VAC	VAC	VAC	VAC	VAC
MAINS CONSUMPTION	W	W	W	W	W	W
NOISE FIGURE	dB	dB	dB	dB	dB	dB
CONNECTION	F	F	F	F	F	F
AUTOMATIC	available 120 mA	available 120 mA	available 120 mA	available 120 mA	available 120 mA	available 120 mA
DC TO PRÉ-AMPL.	Max. Dispon. 120 mA	Max. Dispon. 120 mA	Max. Dispon. 120 mA	Max. Dispon. 120 mA	Max. Dispon. 120 mA	Max. Dispon. 120 mA

*DIN 45004B, IMD3= -60dB, 3P

**EN 50083-3, IMD3= -60dB, 2P