

P | Cabling

Data sheet

DCCS subassembly OM4 6xLC-D/1xMTP-M violet

Page 1/5

P/N

130D217JM0000N


EAN 4251394644998

2021/02/18

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- DCCS housing with incorporated LC MTP fanout for splitting or combining duplex to multi-fiber cables
- 6 LC duplex adapters at the front and one MPO/MTP adapter (key up/key down, type A) mounted at the back
- easy assembly/disassembly in DCCS subrack (19 inch, 1 RU)
- suitable for back side connection of MPO/MTP female trunk cable in customers specific lengths
- housing: galvanized sheet steel, stainless steel front, strain relief via cable ties
- variants: blue (SM), green (SM APC), lime green (OM5), violet (OM4), aqua (OM3)
- all available variants can be created with the configurator



P | Cabling

Data sheet

Page 2/5

DCCS subassembly OM4 6xLC-D/1xMTP-M violet

P/N

130D217JM0000N

EAN 4251394644998

2021/02/18

Technical Data

General Data

Fields of application	Structured building cabling, Office Data center
Design	subassembly / assembly / module / unit
Mounting style	DCCS
Transmission technology	Fiber optic
Port numbering	yes
Color	violet
Dimensions	
Dimension (L x W x H)	186.6 mm x 53.5 mm x 39.6 mm
Dimension (L x W x H)	7.346 in. x 2.106 in. x 1.559 in.
Fiber class	OM4: ISO/IEC 11801/EN 50173 & IEC 60793-2-10/EN 60793-2-10 A1.a.3
Mode type of the fiber	Multimode
Fiber construction	50/125 µm

Connections/interfaces

Connector technology interface 1	LC-D Couplers
Connector technology interface 2	MPO/MTP adapter
Number of ports interface 1	6
Number of ports interface 2	1
Number of equipped ports interface 1	6
Number of ports interface 2 equipped	1
Number of ports with dust protection interface 1	6
Number of ports with dust protection interface 2	6

Mechanical data

Cut-out	DCCS
Connector type	duplex
Life - Number of mating cycles	min. 1000

Materials and material properties

Material - Assembly housing	sheet steel
Material - Assembly housing finish	Zn (zinc)
Material - Sleeve	ceramic, slotted
Material - Coupler housing	Plastics
RoHS	compliant



P | Cabling

Data sheet

Page 3/5

DCCS subassembly OM4 6xLC-D/1xMTP-M violet

P/N

130D217JM0000N

EAN 4251394644998

2021/02/18

Technical Data

Classifications

ETIM 5.0	EC002697
ETIM 6.0	EC002699
ETIM 7.0	EC001129

Packing details

Type of packaging	1 pc(s) / box
-------------------	---------------



P | Cabling

Data sheet

Page 4/5

DCCS subassembly OM4 6xLC-D/1xMTP-M violet

P/N

130D217JM0000N

EAN 4251394644998

2021/02/18

Accessories

P/N	Designation
130D2B1B-E	DCCS2 BGT 19 inch 1RU subrack black
130D2B1G-E	DCCS2 BGT 19 inch 1RU subrack light gray

P | Cabling

Data sheet

Page 5/5

DCCS subassembly OM4 6xLC-D/1xMTP-M violet

P/N

130D217JM0000N

EAN 4251394644998

2021/02/18

Illustrations

Dimensional drawing

