

SSD 2-10 SAT loop-through outlet 10 dB | 5...2200 MHz | CATV | SAT



- ✓ Suitable for return path 5...65 MHz
- ✓ F connector gold-plated
- ✓ With cover plate and frame

Order information

Type	SSD 2-10
Order no.	SSD00210
GTIN	7611682180206
PE	1
VE	1
EU customs tariff number	85291095



Technical data

Tap method	Filter circuit/directional coupler
Trunk line	
Frequency range input	5...2200 MHz
Through loss @ 5...2200 MHz	2...5 dB
Isolation internal	20...40 dB
Frequency range output	5...2200 MHz
Suitable cables (Inner conductor outer diameter)	0.63...1.13 mm 4.70...7.35 mm
TV connector	
Connector type	IEC-male
Frequency range	174...862 MHz 5...65MHz
Tap loss	≤ 10 dB ≤ 11 dB
Radio connector	
Connector type	IEC-female
Frequency range	87.5...125 MHz
Tap loss	≤ 10 dB
SAT connector	
Connector type	F female
Frequency range	950...2200 MHz
DC power pass to trunk	yes
General	
Dimensions (W × H × D) appr.	78 × 78 × 44 mm
Weight	0.149 kg

Suitable products

TZU 3-01 Terminating resistor, DC-isolated