

MegaLine[®] E5-60 U/F Cca

KS-02YSH 4 x 2 x AWG 23/1 PIMF



 Category 6_A **S₄ P₂ A₃ C₄ E₃**


Illustration similar

Construction

Conductor bare copper wire, AWG 23/1
 Insulation cellular-PE, core-Ø: nominal value 1.4 mm
 Colour code wh/bl, wh/or, wh/gn, wh/br
 Element cores to pair
 Pair shielding aluminium-bonded polyester tape


Twisting 4 pairs to cable core with tinned copper wire
 AWG 24/1
 Outer sheath halogen free, flame retardant compound
 Colour Lime green

Cable marking

KERPEN DATACOM Made in Germany MegaLine E5-60 U/F 4P H Cat.6A 4PPoE Cca s1a d0 a1 DoP: CDESK0000043 \$BA-Nr.\$ \$m-sign.\$

Fire Behaviour


Fire class / DoP Cca -s1a,d0,a1 / CDESK0000043
 Fire performance EN 50575 / EN 50399
 Flame retardancy acc. to IEC 60332-3-24
 Halogen-free IEC 60754-1/2
 Acidity IEC 60754-2
 Smoke density IEC 61034-1/2
 Fire load (approx.) 0.6 MJ/m



Security (fire behaviour)

Performance


better than Category 6A acc. to EN 50288 and IEC 61156
 excellent NEXT, well screen properties (pair- and overall screen), low Skew
 Transmission bandwidth (typ.) 600 MHz



Performance (class, bandwidth)

Applications


Installation cable for generic cabling systems acc. to ISO/IEC 11801 and EN 50173 (3rd edition). Ideal for all applications of class D up to EA up to 10 GbE acc. to IEEE 802.3 an, Cable sharing, VoIP, PoE/PoE+/4PPoE.



Application (Ethernet, TV)

Mechanical characteristics (cable)


Bending radius (static) (min.) 4x outer-Ø
 Bending radius (dynamic) (min.) 8x outer-Ø
 Tensile loading (max.) 110 N
 Crush resistance (long term) 1000 N/100mm
 Impact strength (quantity of impacts) 10



Construction (conductor size, tensile strength)

Electromagnetic behaviour

Coupling resistance @ 10 MHz (nom.) 50 mΩ/m
 Screen attenuation (nom.) 55 dB
 Coupling attenuation (nom.) 65 dB
 Segregation class according EN 50174-2 c



EMC (coupling attenuation)

MegaLine[®] E5-60 U/F Cca

KS-02YSH 4 x 2 x AWG 23/1 PIMF

 Category 6_A **S₄ P₂ A₃ C₄ E₃**
Electrical properties at 20°C

DC resistance (max.)	82 Ω/km
Insulation resistance (min.)	5 GΩ x km
Operating capacity (approx.)	42 pF/m
Capacitive coupling (e) (approx.)	1100 pF/km
Signal velocity (approx.)	0.8 x c
Phase delay	420 ns/100m
Skew @ 100 MHz (approx.)	7 ns/100m
Characteristic impedance @ 100 MHz	100 +/- 5 Ω
Test voltage	1000 V
Operating voltage (max.)	125 V

Thermal characteristics (cable)

Temperature (transport / storage)	-20 °C up to +60 °C
Temperature during installation	0 °C up to +50 °C
Temperature after installation	-20 °C up to +60 °C

Chemical characteristics

Free of hazardous substances acc. to RoHS 2011/65/EU

Frequenz MHz	Attenuation dB/100m		NEXT dB		PSNEXT dB		ACR-N dB@100m		PSACR-N dB@100m		ACR-F dB@100m		PSACR-F dB@100m		RL dB	
	typ.	Cat.6 _A max.*	typ.	Cat.6 _A min.*	typ.	Cat.6 _A min.*	typ.	Cat.6 _A min.*	typ.	Cat.6 _A min.*	typ.	Cat.6 _A min.*	typ.	Cat.6 _A min.*	typ.	Cat.6 _A min.*
1	1,9	2,1	95	75,3	92	72,3	93	73,2	90	70,2	91	68	88	65	25,1	-
10	5,2	5,9	90	60,3	87	57,3	85	54,4	82	51,4	96	48	93	45	35,2	25,0
100	17,7	19,1	75	45,3	72	42,3	57	26,2	54	23,2	90	28	87	25	37,2	20,1
200	26,4	27,6	68	40,8	65	37,8	42	13,2	39	10,2	78	22	75	19	31,1	18,0
250	29,9	31,1	66	39,3	63	36,3	36	8,2	33	5,2	75	20	72	17	29,5	17,3
300	31,9	34,3	65	38,1	62	35,1	33	3,8	30	0,8	72	19	69	16	28,3	17,3
450	38,9	42,7	63	35,5	60	32,5	24	-7,2	21	-10,2	69	15	66	12	26,7	17,3
500	41,2	45,3	61	34,8	58	31,8	20	-10,5	17	-13,5	66	14	63	11	26,3	17,3
600	46,2	-	57	-	54	-	11	-	8	-	60	-	57	-	25,8	-

* EN 50288-10-1 (2013)/IEC 61156-5(2020)

Standards, certificates and approvals

Conformity

 to CPR (EU/305/2011)
 acc. to LVD (2014/35/EU)

Link Performance

 KERPEN MegaLine[®] systems and further commercial plug-in connector

Inspection certificate

acc. to DIN 55350-18-4.2.1 bzw. EN 10204

Part number	Weight	copper weight	Outer Ø approx.	Colour
LKD7KS6C0350000	51 kg/km	23 kg/km	6.9 mm	Lime green