


Riser Indoor optical cable for access networks, designed for 6m easy midspan access

Cable Design

Based on FT/RD/WTC/13/02/97 v3.0



- not to scale -

- **Micro-module:** Thin wall tubing (FlexTube®), filled with a suitable compound, housing the optical fibres.
- **Assembly of the micro-modules**
- **Strength members:** glass fibre reinforced plastic material, embedded in the outer sheath.
- **Outer Sheath:** LSZH-FR material. Longitudinal markers in order to position the cable opening window.

This cable is designed for indoor installation on cable tray, in corridors or shafts. Possibility of removing 6m of a module for mid span connexion at the floor without necessity to dispose of an over-length of cable. The fully dry Flextube® design provides easier storage & faster installation. Finger access to the fibres: no specific tools to open the Flextube®.

Technical data

No. of Fibres		48	64
Design		8 x 6	8 x 8
Optical module Ø	mm	1.1	1.2
Cable Diameter	mm	10.5	
Cable Weight	kg / km	105	
Minimum Bending Radius	mm	Without Tension 120	
Temperature Range	°C	Installation -5 -> +45	Transport & Storage -40 -> +70 Operation -5 -> +70

Please refer to our General Installation, Safety & Handling recommendations before handling.

Main characteristics

Test	Test Standard	Specified Value	Acceptance Criteria*
Maximum Tension	IEC 60794-1-2-E1	60 daN	$\Delta\alpha$ reversible, fibre strain $\leq 0.5\%$
Crush	IEC 60794-1-2-E3	15 daN / cm 20 daN / cm	$\Delta\alpha \leq 0.1$ dB, no damage $\Delta\alpha$ reversible
Impact	IEC 60794-1-2-E4	3 Nm (20°C & -5°C)	$\Delta\alpha$ reversible, no damage
Torsion	IEC 60794-1-2-E7	55N, 1m, +/-180°, 10 cycles	$\Delta\alpha \leq 0.1$ dB, no damage
Cable kink	IEC 60794-1-2-E10	R=55mm (20°C & -5°C)	No kink, no damage
Cable bend	IEC 60794-1-2-E11B	R=120mm	$\Delta\alpha \leq 0.1$ dB, no damage
Temperature range	IEC 60794-1-2-F1	-5°C to +60°C -40°C to +70°C	$\Delta\alpha \leq 0.1$ dB/km $\Delta\alpha$ reversible
Fire performance	EN 60332-1-2 NFC 32070-C2		EN 60332-1-2 NFC 32070-C2









* values for single mode fibres, all optical measurements performed at 1550 nm.

Optical Characteristics









According to FT/RD/RESA/06/06/45 Ed4, SD5

Identification

Fibre Colours

No.	1	2	3	4	5	6	7	8
Colour	red	blue	green	yellow	violet	brown	orange	grey
								

Flextube Colours

No.	1	2	3	4	5	6	7	8
Colour	red	blue	green	yellow	violet	white	orange	grey
								

Sheath Colour:

The outer sheath colour is white.

Sheath Marking:

The outer sheath is marked in 1 meter intervals as follows:

**ORANGE DRAKA <ww>-<yyyy> L1095-3 M<no. of fibres/module>
<no. of fibres> FO G657A2 OHC FRC <cable ID> <length marking in meter>**

Logistic

Packing:

Wooden drums with protection.

Delivery Length:

Standard delivery length is 4 km with a tolerance of -1% / +3%

© PrysmianGroup 2013, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorized by PrysmianGroup.