



4G / LTE In- Line Filter



| Ref. | RE-FLTE |
|------|---------|
|------|---------|

| General information |
|---|
| In line LTE filter to cut the frequencies between 790 MHz and 862MHz. The filter must be installed on outdoor and indoor distribution to upgrade the system avoiding the LTE signals. IP66 protection let the use of the filter justbelow the aerials and the SAW tecnology creaata an high selectivity on LTE frequencies. |

| Features |
|--|
| <ul style="list-style-type: none"> • Equipped with a DC pass to enable circuitry • Equipped with F connectors for an optimal signal reception <ul style="list-style-type: none"> • High selectivity on LTE frequencies <ul style="list-style-type: none"> • SAW technology filtering <ul style="list-style-type: none"> • High IP protection • Low insertion loss • High retutn losses |

| Specifications | |
|--------------------|-----------------|
| Application: | DVB-T / DVB-T2 |
| Insertion loss: | 2.7dB |
| Frequency range: | 822-862 MHz |
| Impedance: | 75 Ohm |
| Number of inputs: | 1 |
| Number of outputs: | 1 |
| Material: | Zinc |
| Colour: | Silver |
| Useage: | In Line Filter |
| Connecting type: | 2 x F-Connector |
| IP protection | IP 66 |
| Packaging: | Individual box |
| Master Packaging: | 100 units |
| Brand name: | RELOOK |

GT-SAT International S.A.R.L

16, Rue Millewee

L-7257 Helmsange-Walferdange

Luxembourg

Tel: +352-26432203 Fax: +352-26432204

WEB: www.gt-sat.com