


A-DQ(BN)2Y max. 12F

This cable is suitable for indoor or outdoor installation. Standard rodent protection.



Mechanical and Environmental properties

Test	Value	Unit	Method
Cable outer diameter	5,3 ± 0,5	mm	EN 60811-203
Cable weight	26	kg/km	
Outer jacket thickness	1	mm	
Loose tube diameter	2,3	mm	
Max. tensile strength	1100	N	EN 60794-1-21-E1
Crush resistance test	2000	N	EN 60794-1-21-E3
Impact resistance test	15	Nm	EN 60794-1-21-E4
Min. bend radius (no load)	10	× OD	EN 60794-1-21-E11a
Min. bend radius (load)	15	× OD	EN 60794-1-21-E11b
Moisture resistance test	pass		EN 60794-1-22-F5
Temperature range	Installation	-15 to + 50	EN 60794-1-22-F1
	Operation	-20 to + 70	
	Storage	-20 to + 70	

Cable life time - minimum 30 years

Sheat Marking

Print colour	White
Print method	INK-Jet
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

Other print legends available on request

Fibre colour coding

According to IEC 60304

1	Red	7	Brown
2	Green	8	Violet
3	Blue	9	Turquoise
4	Yellow	10	Black
5	White	11	Orange
6	Grey	12	Pink

Other fibre colour sequences available on request

Packing

Depending on ordered put-up lengths

