

LL-CLOSURE/SQ/HIS-6020/II-24

— Universal re-usable closure, outdoor, square design, cable diameters max. 16 mm, max. 24 splices —

Montage environments: Aerial, burial, wall-mounting, pole-mounting and duct-mounting

Degree of protection: IP68 - absolutely sealed

APPLICATION


Fumo's universal re-usable closures of the SQ-6020 range for fiber optic cables are especially designed to protect cable connections in outdoor applications. They can be used with any cable construction and due to its robust structure and design, it withstands even harshest environments, as well as it's ready for various fiber optic splice applications (*express, tap-off, branch, and repair*). The four cable entries of OV-6020/III can be used for cables with an outer diameter from 8 to 16 mm. The advanced robust design of the body and cover, carrying 1 slide-in-lock splice trays (*max. 24 splices in trays of L170xW120xH14mm and L160xW122xH10mm*), is protected by an elastic waterproof sealing. Accordingly, the closure can be easily re-opened and securely re-closed. In addition, SQ-6020/III has excellent features, such as a high mechanical firmness, acid & corrosion resistance, absolute water-tightness, as well as no special tools and trainings are required for handling and montage.

CABLE BRANCH CLOSURE



TYPE2 splice tray

TECHNICAL SPECIFICATION



DIMENSIONS	: L474 x W222 x H124mm
CABLE DIAMETERS	: variable 8 - 16mm
NUMBER OF CABLE ENTRIES	: 4 (4 x 8 - 16mm)
NUMBER OF SPLICES	: max. 24 on 1 splice trays L170xW120xH14mm order info splice tray: LL-CLOSURE/SQ/HIS-6020/II-TYPE2
MATERIAL OF CLOSURE	: PC (polycarbonate)
COLOR	: black (other colors available on request)
TEMPERATURE RANGE	: -40°C to 65°C
PROOF TEST	: IP68
ACCESSORIES INCLUDED	: 1 roll seal tape 1 roll insulation tape 1 pc. abrasive cloth 1 pc. earth wire 1 set nylon ties 2 bags desiccant 1 pc. measuring tape 1 pc. hexagon wrench 1 set mounting hooks 1 bag heat-shrink protection sleeves
OPTIONAL ACCESSORIES	: 1 pc. pressure testing valve 1 pc. earth deriving device 1 roll buffer tube, either for bunchy or ribbon fibers 1 set pole-mounting brackets 1 set wall-mounting brackets 1 roll buffer-tube for ribbon fiber

PACKAGING

1 piece in robust, ship-worthy carton box

© Fumo2018. All Rights Reserved. – All values in this data sheet are nominal.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Fumo. The information is believed correct at the time of issue. Fumo reserves the right to amend this specification without notice. Specification is not contractually valid unless specifically authorized by Fumo.

Rev. 11/2020



Fumo Communications
FUMO COMMUNICATIONS

