

LL-CLOSURE/OV/HIS-6001/II-144

— Universal re-usable closure, outdoor, cable diameters 16, 20 & 23mm, max. 144 splices —

Montage environments: Aerial, burial, wall-mounting, pole-mounting and duct-mounting


Degree of protection: IP68 - absolutely sealed

APPLICATION


Fumo’s universal re-usable closures of the OV6001 range for fiber optic cables are especially designed to protect cable connections in outdoor applications. They can be used with any cable construction and due to its robust structure and design, it withstands even harshest environments, as well as it’s ready for various fiber optic splice applications (*express, tap-off, branch, and repair*).

The six cable entries of OV-6001/II can be used for cables with an outer diameter of 16, 20 and 23 mm. The advanced oval design of the body and cover, able to carry up to 6 slide-in-lock splice trays (*max. 144 splices in trays of L160xW122xH10mm*), is protected by an elastic waterproof sealing. Accordingly, the closure can be easily re-opened and securely re-closed. In addition, OV-6001/II has excellent features, such as a high mechanical firmness, acid & corrosion resistance, absolute water-tightness, as well as no special tools and trainings are required for handling and montage.

CABLE BRANCH CLOSURE



TECHNICAL SPECIFICATION



DIMENSIONS	: L444 x W220 x H132mm
CABLE DIAMETERS	: 16mm, 20mm & 23mm
NUMBER OF CABLE ENTRIES	: 6 (2 x 16mm, 2 x 20mm, 2 x 23mm)
NUMBER OF SPLICES	: max. 144 on max. 6 splice trays L160xW122xH10mm order info splice tray: LL-CLOSURE/OV/HIS-6001/II-TYPE2
MATERIAL OF CLOSURE	: PC (polycarbonate)
COLOR	: black (other colors available on request)
TEMPERATURE RANGE	: -40°C to 65°C
PROOF TEST	: IP68
ACCESSORIES INCLUDED	: 1 roll seal tape 1 roll insulation tape 1 pc. abrasive cloth 1 pc. earth wire 1 set nylon ties 2 bags desiccant 1 pc. measuring tape 1 pc. dedicated wrench 2 pcs. hexagon wrenches 1 set mounting hooks 1 bag heat-shrink protection sleeves
OPTIONAL ACCESSORIES	: 1 pc. pressure testing valve 1 pc. earth deriving device 1 roll buffer tube, either for bunchy or ribbon fibers 1 set pole-mounting brackets 1 set wall-mounting brackets

PACKAGING

1 piece in robust, ship-worthy carton box

© Fumo2018. All Rights Reserved. – All values in this data sheet are nominal.  
The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Fumo. The information is believed correct at the time of issue. Fumo reserves the right to amend this specification without notice. Specification is not contractually valid unless specifically authorized by Fumo.

Rev. 04/2020

