

# Fiber Optic Distribution Box FA-MP5

**FA-MP5-96-24-47-K96-GY-UMK**

Fiber Optic Distribution Box with cross panel for FTTH solutions.



Termination Box FA-MP5

## features:

- capacity up to 96 splices,
- system of 4 hinged splice trays, each for 24 splices with additional place for 1x8 and 1x16 PLC splitter mini metal box package,
- 1 oval line port (possibility to assemble cables with uncut tubes),
- 2 round line ports,
- 24 round subscriber ports,
- cross panel for 24 SC simplex adapters,
- indoor and outdoor use,
- pole mounting by using dedicated cross cable storage FA-SZ-5,
- velcro tape blocking accidental trays opening,
- door opened upside, side buckles, screw lock,
- possibility to expand capacity up to 144 splices, by removing cross panel.

## sectors:



TELECOMMUNICATION  
AND MOBILE  
OPERATORS



DATA TRANSMISSION  
OPERATORS



ISP AND CATV  
OPERATORS



ENERGETICS



DESIGN AND  
EXECUTION  
COMPANIES



DEVELOPERS

## technical specifications:

FA-MP5-96-24-K96-GY-UMK	
dimensions (width x height. x depth)[mm]	212 x 353 x 106
cross panel capacity	24 SC simplex (or 24 LC duplex)
number of splices	96
cable diameter [mm]	oval line 1 pc. (cable Ø8-15)
	round line 2 pcs. (cable Ø6 - 12), cable gland PG13,5
	round subscriber 24 pcs. (cable Ø5 - 8), hole of the port Ø11,5mm, suitable for preconnectorized subscriber drop cable
IP protect	IP65
material	ABS + PC